

# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

## \*\*\* Section 1 - Chemical Product and Company Identification \*\*\*

**Chemical Formula:** Mixture

**Product Use:** Various fabricated aluminum parts and products.

**Other Designations:** 3xxx Series Alloys, 3xxx Cladding, 0033, 0333CU, 3003F, 3003-C06C, 3005, 3030-C98C, 3104BLND, C08A, C77A, C15B, C20B, C35B, C46B, C56B, C59B, C91B, C92B, C93B, C94B, C13C, C02D, C06D, C13D, C14D, C18D, C48D, C06E, C17E, C19E, C23E, C26E, C27E, C35E, C47E, C48E, C54E, C57E, C58E, C59E, C70E, C71E, C72E, C73E, C12H, C26H, C27H, C29H, C38H, C39H, C44H, C58H, C76H, C03N, C05N, C31N, C32N, C34N, C35N, C38N, C156, C162, C189, C229, C300, C301, C784, C786, C98C, CH14, CK32, CU54, CU55, 3PORC, Alclad 3003, Alclad 3004, Clad 3003, KB11, MC365, MC369, MC370, MC371, MC372, MC373, MC374, MC378, MC380, MC382, MC386, MC387, MC389, MC392, MC395, MC396, MC398, MC399, MC400, MC401, MC402, MC403, MC404, MC405, MC406, MC413, MC414, MC424, MC425, MD52, MD176, MD189, MD228, MD229, MD239, MD240, MD241, MD243, MD263RB, MD263RH, MD263RL, MD267, MD268, MD271, MD272, MD276, MD278, MD281, MD285, MD286, MD287, MD288, MD289, MD291, MD297, MD299, MD305, MD306, MD307, MD308, MD310, MD311, MD312, MD313, MD314, MD315, MD321, MD324, MD327, MD329, MD330, MD333, MD334, MD338, MD339, MD340, MD341, MD347, MD350, MD351, MD352, MD354, MD355, MD356, MD357, MD359, MD360, MD362, MN363, MN381, MN397, MN421, MN422, MN423, MN427, MN428, RA108, RA135, RA169, RA173, RA190, RA203, RA211, RA220, RA236, RA240, RA245, RA254, RA258, RA259, RA261, RA263, RA264, RA269, RA270, X301.

Alcoa Inc.  
201 Isabella Street  
Pittsburgh, PA 15212-5858

Phone: Health and Safety: 1-412-553-4649

**Emergency Information:** USA: Chemtrec: 1-800-424-9300 or 1-703-527-3887

Alcoa: 1-412-553-4001

**Website:** For a current MSDS, refer to Alcoa websites: [www.alcoa.com](http://www.alcoa.com) or Internally at [my.alcoa.com](http://my.alcoa.com) EHS Community

## \*\*\* Section 2 - Hazards Identification \*\*\*

### EMERGENCY OVERVIEW

Solid. Silvery. Odorless. Non-combustible as supplied. Small chips, fine turnings and dust from processing may be readily ignitable.

Explosion/fire hazards may be present when (See Sections 5, 7 and 10 for additional information):

- \* Dust or fines are dispersed in the air.
- \* Chips, dust or fines are in contact with water.
- \* Dust or fines are in contact with certain metal oxides (e.g. rust).
- \* Molten metal is in contact with water/moisture or certain metal oxides (e.g. rust).

Dust and fume from processing can cause irritation of eyes, skin and upper respiratory tract and metal fume fever.

### POTENTIAL HEALTH EFFECTS

The following statements summarize the health effects generally expected in cases of overexposures. User specific situations should be assessed by a qualified individual. Additional health information can be found in Section 11.

The health effects listed below are not likely to occur unless processing of this product generates dust or fumes.

**Eyes:** Dust or fume from processing: Can cause irritation.

#### Skin

Contact with residual oil/oil coating: Can cause irritation. Prolonged or repeated contact with the skin can cause dermatitis.

Dust or fume from processing: Can cause sensitization and allergic contact dermatitis.

# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

## Inhalation

Health effects from mechanical processing (e.g., cutting, grinding): Can cause irritation of respiratory tract.

**Chronic overexposures:** Can cause respiratory sensitization, scarring of the lungs (pulmonary fibrosis), central nervous system effects, secondary Parkinson's disease and reproductive harm in males.

Additional health effects from elevated temperature processing (e.g., welding, melting): **Acute overexposures:** Can cause nausea, fever, chills, shortness of breath and malaise (metal fume fever), bronchitis, reduced ability of the blood to carry oxygen (methemoglobin) and the accumulation of fluid in the lungs (pulmonary edema).

**Chronic overexposures:** Can cause scarring of the lungs (pulmonary fibrosis).

## Carcinogenicity and Reproductive Hazard

Product as shipped: Does not present any cancer or reproductive hazards.

Dust and fumes from mechanical processing: Can present a cancer hazard (nickel). Can present a reproductive hazard for males (manganese).

Dust and fumes from welding or elevated temperature processing: Can present a cancer hazard (nickel compounds, hexavalent chromium, welding fumes). Can present a reproductive hazard for males (manganese).

## Medical Conditions Aggravated By Exposure to Product, Components or Compounds Formed During Processing

Dust or fume from processing: Asthma, chronic lung disease, skin rashes and secondary Parkinson's disease.

### \*\*\* Section 3 - Composition / Information on Ingredients \*\*\*

Complete composition is provided below and may include some components classified as non-hazardous.

CAS #	Component	Percent
7429-90-5	Aluminum	>92
7439-95-4	Magnesium	<2.8
7439-96-5	Manganese	<2
7440-21-3	Silicon	<1.9
7440-66-6	Zinc	<1.8
7440-47-3	Chromium	<0.6
7440-02-0	Nickel	0-0.05

**Component Information:** Additional compounds which may be formed during processing are listed in Section 8.

### \*\*\* Section 4 - First Aid Measures \*\*\*

#### First Aid: Eyes

Dust or fume from processing: Flush eyes with plenty of water or saline for at least 15 minutes. Consult a physician.

#### First Aid: Skin

Dust or fume from processing or contact with lubricant/residual oil: Wash skin with soap and water for at least 15 minutes. Consult a physician if irritation persists.

#### First Aid: Inhalation

Dust or fume from processing: Remove to fresh air. If unconscious or severely injured, check for clear airway, breathing and presence of pulse. Perform CPR if there is no pulse or respiration. Consult a physician.

### \*\*\* Section 5 - Fire Fighting Measures \*\*\*

#### Flammable/Combustible Properties

This product does not present fire or explosion hazards as shipped. Small chips, turnings, dust and fines from processing may be readily ignitable.

#### Fire/Explosion: May be a potential hazard under the following conditions:

\* Dust or fines dispersed in the air can be explosive. Even a minor dust cloud can explode violently. Dust accumulation on the floor, ledges and beams can present a risk of ignition, flame propagation and secondary explosions.

# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

\* Chips, dust or fines in contact with water can generate flammable/explosive hydrogen gas. Hydrogen gas could present an explosion hazard in confined or poorly ventilated spaces.

\* Dust or fines in contact with certain metal oxides (e.g., rust). A thermite reaction, with considerable heat generation, can be initiated by a weak ignition source.

\* Molten metal in contact with water/moisture or other metal oxides (e.g., rust, copper oxide). Moisture entrapped by molten metal can be explosive. Contact of molten aluminum with other metal oxides can initiate a thermite reaction. Finely divided metals (e.g., powders or wire) may have enough surface oxide to produce thermite reactions/explosions.

## Extinguishing Media

Use Class D extinguishing agents on dusts, fines or molten metal. Use coarse water spray on chips and turnings.

## Unsuitable Extinguishing Media

DO NOT USE:

\* Halogenated agents on small chips, dusts or fines.

\* Water around molten metal.

These agents will react with the burning material.

## Fire Fighting Equipment/Instructions

Fire fighters should wear NIOSH approved, positive pressure, self-contained breathing apparatus and full protective clothing when appropriate.

## \*\*\* Section 6 - Accidental Release Measures \*\*\*

### Small/Large Spill

*If molten:* Contain the flow using dry sand or salt flux as a dam. Do not use shovels or hand tools to halt the flow of molten aluminum. Allow the spill to cool before remelting as scrap.

## \*\*\* Section 7 - Handling and Storage \*\*\*

### Handling/Storage

Product should be kept dry. Avoid generating dust. Avoid contact with sharp edges or heated metal. Hot and cold aluminum are not visually different. Hot aluminum does not necessarily glow red.

### Requirements for Processes Which Generate Dusts or Fumes

If processing of these products includes operations where dust or extremely fine particulate is generated, obtain and follow the safety procedures and equipment guides contained in Aluminum Association Bulletin F-1 and National Fire Protection Association (NFPA) brochures listed in Section 16. Cover and reseal partially empty containers. Use non-sparking handling equipment. Provide grounding and bonding where necessary to prevent accumulation of static charges during dust handling and transfer operations. (See Section 15).

Local ventilation and vacuum systems must be designed to handle explosive dusts. Dry vacuums and electrostatic precipitators must not be used. Dust collection systems must be dedicated to aluminum dust only and should be clearly labeled as such. Do not co-mingle fines of aluminum with fines of iron, iron oxide (rust) or other metal oxides.

Do not allow chips, fines or dust to contact water, particularly in enclosed areas.

Avoid all ignition sources. Good housekeeping practices must be maintained. Do not use compressed air to remove settled material from floors, beams or equipment.

### Requirements for Remelting of Scrap Material and/or Ingot

Molten metal and water can be an explosive combination. The risk is greatest when there is sufficient molten metal to entrap or seal off the water. Water and other forms of contamination on or contained in scrap or remelt ingot are known to have caused explosions in melting operations. While the products may have minimal surface roughness and internal voids, there remains the possibility of moisture contamination or entrapment. If confined, even a few drops of water can lead to violent explosions.

# Material Safety Data Sheet

Product Name: **WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS**

ID: 665

All tooling and containers which come in contact with molten metal must be preheated or specially coated and rust free. Molds and ladles must be preheated or oiled prior to casting. Any surfaces that may contact molten metal (e.g., concrete) should be specially coated.

Drops of molten metal in water (e.g. from plasma arc cutting), while not normally an explosion hazard, can generate enough flammable hydrogen gas to present an explosion hazard. Vigorous circulation of the water and removal of the particles minimize the hazards.

During melting operations, the following minimum guidelines should be observed:

- \* Inspect all materials prior to furnace charging and completely remove surface contamination such as water, ice, snow, deposits of grease and oil or other surface contamination resulting from weather exposure, shipment, or storage.
- \* Store materials in dry, heated areas with any cracks or cavities pointed downwards.
- \* Preheat and dry large or heavy items such as ingot adequately before charging into a furnace containing molten metal. This is typically done by use of a drying oven or homogenizing furnace. The drying cycle should bring the internal metal temperature of the coldest item of the batch to 400°F and then hold at that temperature for 6 hours.

## \*\*\* Section 8 - Exposure Controls / Personal Protection \*\*\*

### Engineering Controls

If dust or fumes are generated through processing: Use with adequate explosion-proof ventilation to meet the limits listed in Section 8, Exposure Guidelines.

### Personal Protective Equipment

#### Respiratory Protection

If dust or fumes are generated through processing: Use NIOSH-approved respiratory protection as specified by an Industrial Hygienist or other qualified professional if concentrations exceed the limits listed in Section 8, Exposure Guidelines. Suggested respiratory protection: P95

**Eye Protection:** Wear safety glasses/goggles to avoid eye contact.

#### Skin Protection

Wear impervious gloves to avoid repeated or prolonged skin contact with residual oils and to avoid any skin injury.

### General

Personnel who handle and work with **molten metal** should utilize primary protective clothing like polycarbonate face shields, fire resistant tapper's jackets, neck shades (snoods), leggings, spats and similar equipment to prevent burn injuries. In addition to primary protection, secondary or day-to-day work clothing that is fire resistant and sheds metal splash is recommended for use with molten metal. Synthetic materials should never be worn even as secondary clothing (undergarments).

Minimize breathing **oil vapors and mist**. Remove oil contaminated clothing; launder or dry-clean before reuse. Remove oil contaminated shoes and thoroughly clean and dry before reuse. Cleanse skin thoroughly after contact, before breaks and meals, and at the end of the work period. Oil coating is readily removed from skin with waterless hand cleaners followed by a thorough washing with soap and water.

### Exposure Guidelines

#### A: General Product Information

Alcoa recommends an Occupational Exposure Limit for **Nickel Compounds** of 0.1 mg/m<sup>3</sup> TWA.

Alcoa recommends an Occupational Exposure Limit for **Chromium (VI) Compounds [both soluble and insoluble forms]** of 0.25 ug/m<sup>3</sup> TWA as chromium.

Alcoa recommends an Occupational Exposure Limit for **Oil Mist** of 0.5 mg/m<sup>3</sup> TWA.

Alcoa recommends Occupational Exposure Limits for **Manganese** of 0.05 mg/m<sup>3</sup> TWA (total particulate) and 0.02 mg/m<sup>3</sup> TWA (respirable fraction).

#### B: Component Exposure Limits

##### Aluminum (7429-90-5)

ACGIH 10 mg/m<sup>3</sup> TWA (metal dust)

OSHA 15 mg/m<sup>3</sup> TWA (total dust); 5 mg/m<sup>3</sup> TWA (respirable fraction)

##### Manganese (7439-96-5)

ACGIH 0.2 mg/m<sup>3</sup> TWA

OSHA 5 mg/m<sup>3</sup> Ceiling (fume)

# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

## Silicon (7440-21-3)

OSHA 15 mg/m<sup>3</sup> TWA (total dust); 5 mg/m<sup>3</sup> TWA (respirable fraction)

## Chromium (7440-47-3)

ACGIH 0.5 mg/m<sup>3</sup> TWA

OSHA 1 mg/m<sup>3</sup> TWA

## Nickel (7440-02-0)

ACGIH 1.5 mg/m<sup>3</sup> TWA (inhalable fraction)

OSHA 1 mg/m<sup>3</sup> TWA

## C: Exposure Limits for Additional Compounds Which May Be Formed During Processing

### Alumina (non-fibrous) (1344-28-1)

ACGIH 10 mg/m<sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica)

OSHA 15 mg/m<sup>3</sup> TWA (total dust); 5 mg/m<sup>3</sup> TWA (respirable fraction)

### Magnesium oxide fume (1309-48-4)

ACGIH 10 mg/m<sup>3</sup> TWA (inhalable fraction)

OSHA 15 mg/m<sup>3</sup> TWA (total particulate)

### Manganese inorganic compounds (Not Available)

ACGIH 0.2 mg/m<sup>3</sup> TWA (as Mn) (related to Manganese compounds, inorganic)

OSHA 5 mg/m<sup>3</sup> Ceiling (as Mn)

### Zinc oxide (1314-13-2)

ACGIH 2 mg/m<sup>3</sup> TWA (respirable fraction)

ACGIH 10 mg/m<sup>3</sup> STEL (respirable fraction)

OSHA 5 mg/m<sup>3</sup> TWA (fume); 15 mg/m<sup>3</sup> TWA (total dust); 5 mg/m<sup>3</sup> TWA (respirable fraction)

### Chromium (II) compounds (Not Available)

OSHA 0.5 mg/m<sup>3</sup> TWA (as Cr)

### Chromium (III) compounds (Not Available)

ACGIH 0.5 mg/m<sup>3</sup> TWA (as Cr)

OSHA 0.5 mg/m<sup>3</sup> TWA (as Cr)

### Chromium (VI) compounds- water soluble (Not Available)

ACGIH 0.05 mg/m<sup>3</sup> TWA (as Cr)

### Chromium (VI) compounds (certain water insoluble forms) (Not Available)

ACGIH 0.01 mg/m<sup>3</sup> TWA (as Cr)

OSHA 5 µg/m<sup>3</sup> TWA

OSHA 2.5 µg/m<sup>3</sup> Action Level (as Cr.); 5 µg/m<sup>3</sup> TWA (as Cr. Cancer hazard - See 29 CFR 1910.1026)

### Nickel insoluble compounds (Not Available)

ACGIH 0.2 mg/m<sup>3</sup> TWA (inhalable fraction, as Ni) (related to Nickel insoluble inorganic compounds (NOS))

OSHA 1 mg/m<sup>3</sup> TWA (as Ni)

### Oil mist, mineral (8012-95-1)

ACGIH 5 mg/m<sup>3</sup> TWA (sampled by method that does not collect vapor)

ACGIH 10 mg/m<sup>3</sup> STEL

OSHA 5 mg/m<sup>3</sup> TWA

### Ozone (10028-15-6)

ACGIH 0.05 ppm TWA (heavy work); 0.08 ppm TWA (moderate work); 0.10 ppm TWA (light work); 0.20 ppm TWA (heavy, moderate or light workloads, <=2 hours)

OSHA 0.1 ppm TWA; 0.2 mg/m<sup>3</sup> TWA

### Nitrogen dioxide (10102-44-0)

ACGIH 3 ppm TWA

ACGIH 5 ppm STEL

OSHA 5 ppm Ceiling; 9 mg/m<sup>3</sup> Ceiling

### Nitric oxide (10102-43-9)

ACGIH 25 ppm TWA

OSHA 25 ppm TWA; 30 mg/m<sup>3</sup> TWA

# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

## \*\*\* Section 9 - Physical & Chemical Properties \*\*\*

<b>Physical State:</b> Solid: sheet, plate, wire, rod, bar, extrusion, forgings, etc.	<b>Appearance:</b> Silvery
<b>Boiling Point:</b> Not applicable	<b>Melting Point:</b> Range: generally 1150-1220°F (621-660°C)
<b>Vapor Pressure:</b> Not applicable	<b>Vapor Density:</b> Not applicable
<b>Solubility in Water:</b> None	<b>Specific Gravity:</b> See Density
<b>Density:</b> Range: generally 2.70-2.75 g/cm <sup>3</sup> (0.098-0.099 lb/in <sup>3</sup> )	<b>pH Level:</b> Not applicable
<b>Odor:</b> None	<b>Odor Threshold:</b> Not applicable
<b>Octanol-Water Coefficient:</b> Not applicable	

## \*\*\* Section 10 - Chemical Stability & Reactivity Information \*\*\*

**Stability:** Stable under normal conditions of use, storage, and transportation as shipped.

### Conditions to Avoid

Chips, fines, dust and molten metal are considerably more reactive with the following:

- \* **Water:** Slowly generates flammable/explosive hydrogen gas and heat. Generation rate is greatly increased with smaller particles (e.g., fines and dusts). Molten metal can react violently/explosively with water or moisture, particularly when the water is entrapped.
- \* **Heat:** Oxidizes at a rate dependent upon temperature and particle size.
- \* **Strong oxidizers:** Violent reaction with considerable heat generation. Can react explosively with nitrates (e.g., ammonium nitrate and fertilizers containing nitrate) particularly when heated or molten.
- \* **Acids and alkalis:** Reacts to generate flammable/explosive hydrogen gas. Generation rate is greatly increased with smaller particles (e.g., fines and dusts).
- \* **Halogenated compounds:** Many halogenated hydrocarbons, including halogenated fire extinguishing agents, can react violently with finely divided aluminum.
- \* **Iron oxide (rust) and other metal oxides (e.g., copper and lead oxides):** A violent thermite reaction generating considerable heat can occur. Reaction with aluminum fines and dusts requires only very weak ignition sources for initiation. Molten aluminum can react violently with iron oxide without external ignition source.
- \* **Iron powder and water:** An explosive reaction forming hydrogen gas occurs when heated above 1470°F (800°C).

Thermite explosions have been reported when aluminum alloys were melted in furnaces used for alloying with lead, bismuth or other metals with low melting temperatures. These metals, when added as high purity ingots, can seep through cracks in furnace liners and become oxidized. During subsequent melts in the furnace, molten aluminum can contact these metal oxides resulting in a thermite explosion.

## \*\*\* Section 11 - Toxicological Information \*\*\*

### Health Effects Associated with Individual Ingredients

**Chromium dust and mist** Can cause irritation of eyes, skin and respiratory tract. **Chromium and trivalent chromium** IARC/NTP: Not classified by IARC.

**Nickel dust and fumes** Can cause irritation of eyes, skin and respiratory tract. Eye contact: Can cause inflammation of the eyes and eyelids (conjunctivitis). Skin contact: Can cause sensitization and allergic contact dermatitis. Chronic overexposures: Can cause perforation of the nasal septum, inflammation of the nasal passages (sinusitis), respiratory sensitization, asthma and scarring of the lungs (pulmonary fibrosis). **Nickel alloys** IARC/NTP: Reviewed but not recommended for listing by the NTP. Listed as possibly carcinogenic to humans by IARC (Group 2B)\*.

**Manganese dust or fumes** Chronic overexposures: Can cause inflammation of the lung tissue, scarring of the lungs (pulmonary fibrosis), central nervous system damage, secondary Parkinson's disease and reproductive harm in males.

# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

**Silicon, inert dusts** Chronic overexposures: Can cause chronic bronchitis and narrowing of the airways.

**Aluminum dust, fines and fumes** Low health risk by inhalation. Generally considered to be biologically inert (milling, cutting, grinding).

Some products are supplied with a lubricant/oil coating or have residual oil from the manufacturing process. **Oil** Can cause irritation of skin. Skin contact (prolonged or repeated): Can cause dermatitis.

## Health Effects Associated with Individual Compounds Formed During Processing (The following could be expected if welded, remelted or otherwise processed at elevated temperatures.)

**Hexavalent chromium (Chrome VI)** Can cause irritation of eyes, skin and respiratory tract. Skin contact: Can cause irritant dermatitis, allergic reactions and skin ulcers. Chronic overexposures: Can cause perforation of the nasal septum, respiratory sensitization, asthma, the accumulation of fluid in the lungs (pulmonary edema), lung damage, kidney damage, lung cancer, nasal cancer and cancer of the gastrointestinal tract. IARC/NTP: Listed as "known to be a human carcinogen" by the NTP. Listed as carcinogenic to humans by IARC (Group 1)\*.

**Nickel compounds** Associated with lung cancer, cancer of the vocal cords and nasal cancer. IARC/NTP: Listed as "known to be a human carcinogen" by the NTP. Listed as carcinogenic to humans by IARC (Group 1)\*.

**Magnesium oxide fumes** Can cause irritation of eyes and respiratory tract. Acute overexposures: Can cause nausea, fever, chills, shortness of breath and malaise (metal fume fever).

**Manganese oxide fumes** Can cause irritation of eyes, skin and respiratory tract. Acute overexposures: Can cause nausea, fever, chills, shortness of breath and malaise (metal fume fever).

**Zinc oxide fumes** Can cause irritation of upper respiratory tract. Acute overexposures: Can cause nausea, fever, chills, shortness of breath and malaise (metal fume fever). **Zinc oxide dust** Expected to be a low health risk by inhalation.

**Silica, amorphous** Acute overexposures: Can cause dryness of eyes, nose and upper respiratory tract.

**Alumina (aluminum oxide)** Low health risk by inhalation. Generally considered to be biologically inert.

If the product is heated well above ambient temperatures or machined, oil vapor or mist may be generated. **Oil vapor and mist** Can cause irritation of respiratory tract. Acute overexposures: Can cause bronchitis, headache, central nervous system effects (nausea, dizziness and loss of coordination) and drowsiness (narcosis).

Welding, plasma arc cutting, and arc spray metalizing can generate ozone. **Ozone** Can cause irritation of eyes, nose and upper respiratory tract. Acute overexposures: Can cause shortness of breath, tightness of chest, headache, cough, nausea and narrowing of airways. Effects are reversible on cessation of exposure. Acute overexposures (high concentrations): Can cause respiratory distress, respiratory tract damage, bleeding and the accumulation of fluid in the lungs (pulmonary edema). Effects can be delayed up to 1-2 hours. Additional information: Studies with experimental animals by inhalation have found genetic damage, reproductive harm, blood cell damage, lung damage and death.

**Welding fumes** IARC/NTP: Listed as possibly carcinogenic to humans by IARC (Group 2B)\*.

Plasma arc cutting can generate oxides of nitrogen. **Oxides of nitrogen (NO and NO<sub>2</sub>)** Can cause irritation of eyes, skin and respiratory tract. Acute overexposures: Can cause reduced ability of the blood to carry oxygen (methemoglobin). Can cause cough, shortness of breath, the accumulation of fluid in the lungs (pulmonary edema) and death. Effects may be delayed up to 2-3 weeks. **Nitrogen dioxide (NO<sub>2</sub>)** Chronic overexposures: Can cause scarring of the lungs (pulmonary fibrosis).

# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

## Acute Toxicity of Ingredients/Formed Compounds

### A: General Product Information

No information available for product.

### B: Component Analysis - LD50/LC50

**Magnesium (7439-95-4)**

Oral LD50 Rat: 230 mg/kg

**Manganese (7439-96-5)**

Oral LD50 Rat: 9 g/kg

**Silicon (7440-21-3)**

Oral LD50 Rat: 3160 mg/kg

**Nickel (7440-02-0)**

Oral LD50 Rat: >9000 mg/kg

### C: Formed Compound Toxicity - LD50s/LC50s

**Alumina (non-fibrous) (1344-28-1)**

Oral LD50 Rat: >5000 mg/kg

**Zinc oxide (1314-13-2)**

Oral LD50 Rat: >5000 mg/kg

**Oil mist, mineral (8012-95-1)**

Oral LD50 Mouse: 22 g/kg

**Ozone (10028-15-6)**

Inhalation LC50 Rat: 4800 ppb/4H

**Nitrogen dioxide (10102-44-0)**

Inhalation LC50 Rat: 88 ppm/4H

**Nitric oxide (10102-43-9)**

Inhalation LC50 Rat: 1068 mg/m<sup>3</sup>/4H

## Carcinogenicity of Ingredients

### A: Ingredient Carcinogenicity - IARC/NTP

Component	CAS	IARC 1	IARC 2A	IARC 2B	IARC 3	IARC 4	NTP K	NTP RA
Chromium	7440-47-3	No	No	No	Yes	No	No	No
Nickel	7440-02-0	No	No	Yes	No	No	No	No

### B: Ingredient Carcinogenicity - ACGIH

**Chromium (7440-47-3)**

ACGIH A4 - Not Classifiable as a Human Carcinogen

**Nickel (7440-02-0)**

ACGIH A5 - Not Suspected as a Human Carcinogen

### C: Ingredient References

**Chromium (7440-47-3)**

IARC Monograph 49 [1990] (listed under Chromium and Chromium compounds) Supplement 7 [1987]

**Nickel (7440-02-0)**

IARC Monograph 49 [1990], Supplement 7 [1987]

## Carcinogenicity of Compounds Formed During Processing

### A: Formed Compound Carcinogenicity - IARC/NTP

Component	CAS	IARC 1	IARC 2A	IARC 2B	IARC 3	IARC 4	NTP K	NTP RA
Chromium (III) compounds	Not Available	No	No	No	Yes	No	No	No
Chromium (VI) compounds (certain water insoluble forms)	Not Available	Yes	No	No	No	No	Yes	No
Nickel compounds	Not Available	Yes	No	No	No	No	Yes	No
Oil mist, mineral	8012-95-1	No	No	No	Yes	No	No	No
Welding fumes (NOC)	Not Available	No	No	Yes	No	No	No	No



# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

## B: Formed Compound Carcinogenicity - ACGIH

### Alumina (non-fibrous) (1344-28-1)

ACGIH A4 - Not Classifiable as a Human Carcinogen

### Magnesium oxide fume (1309-48-4)

ACGIH A4 - Not Classifiable as a Human Carcinogen

### Chromium (III) compounds (Not Available)

ACGIH A4 - Not Classifiable as a Human Carcinogen

### Chromium (VI) compounds- water soluble (Not Available)

ACGIH A1 - Confirmed Human Carcinogen

### Chromium (VI) compounds (certain water insoluble forms) (Not Available)

ACGIH A1 - Confirmed Human Carcinogen

### Nickel insoluble compounds (Not Available)

ACGIH A1 - Confirmed Human Carcinogen (related to Nickel, inorganic compounds, insoluble (NOS))

### Ozone (10028-15-6)

ACGIH A4 - Not Classifiable as a Human Carcinogen (heavy, moderate, or light workloads)

### Nitrogen dioxide (10102-44-0)

ACGIH A4 - Not Classifiable as a Human Carcinogen

## C: Formed Compound References

### Chromium (III) compounds (Not Available)

IARC Monograph 49 [1990] (listed under Chromium and Chromium compounds) Supplement 7 [1987]

### Chromium (VI) compounds (certain water insoluble forms) (Not Available)

IARC Monograph 49 [1990] (evaluated as a group)

### Nickel compounds (Not Available)

IARC Monograph 49 [1990] (evaluated as a group)

### Oil mist, mineral (8012-95-1)

IARC Supplement 7 [1987], Monograph 33 [1984]

### Welding fumes (NOC) (Not Available)

IARC Monograph 49 [1990]

## Descriptions of IARC and NTP Classifications

**IARC 1:** The agent is carcinogenic to humans. There is sufficient evidence that a causal relationship existed between exposure to the agent and human cancer.

**IARC 2A:** The agent is probably carcinogenic to humans. Generally includes agents for which there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

**IARC 2B:** The agent is possibly carcinogenic to humans. Generally includes agents for which there is limited evidence in humans and less than sufficient evidence in experimental animals.

**IARC 3:** The agent is not classifiable as to its carcinogenicity to humans. Generally includes agents for which there is inadequate evidence in humans and inadequate or limited evidence in experimental animals.

**IARC 4:** The agent is probably not carcinogenic to humans. Generally includes agents for which there is evidence suggesting lack of carcinogenicity in humans and in experimental animals.

**NTP K:** Known to be a human carcinogen.

**NTP RA:** Reasonably anticipated to be a human carcinogen.

## \*\*\* Section 12 - Ecological Information \*\*\*

### Ecotoxicity

#### A: General Product Information

No information available for product.

#### B: Component Analysis - Ecotoxicity - Aquatic Toxicity

##### Zinc (7440-66-6)

96 Hr LC50 Pimephales promelas: 6.4 mg/L

96 Hr EC50 Selenastrum capricornutum: 30 µg/L

72 Hr EC50 water flea: 5 µg/L

# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

## Nickel (7440-02-0)

96 Hr LC50 Oncorhynchus mykiss: 31.7 mg/L (adult); 96 Hr LC50 Pimephales promelas: 3.1 mg/L; 96 Hr LC50 Brachydanio rerio: >100 mg/L  
72 Hr EC50 freshwater algae (4 species): 0.1 mg/L; 72 Hr EC50 Selenastrum capricornutum: 0.18 mg/L  
96 Hr EC50 water flea: 510 µg/L

**Environmental Fate:** No information available for product.

### \*\*\* Section 13 - Disposal Considerations \*\*\*

#### Disposal Instructions

Reuse or recycle material whenever possible. Material may be disposed of at an industrial landfill.

#### US EPA Waste Number & Descriptions

##### A: General Product Information

RCRA Status: Must be determined at time material is disposed. If material is disposed as waste, it must be characterized under RCRA according to 40 CFR, Part 261, or state equivalent in the U.S.

##### B: Component Waste Numbers

RCRA waste codes other than described under Section A may apply depending on use of product. Refer to 40 CFR 261 or state equivalent in the U.S.

### \*\*\* Section 14 - Transportation Information \*\*\*

#### Special Transportation

	PSN #1	PSN #2	PSN #3	PSN #4
Notes:	(1)			
Proper Shipping Name:	Not regulated			
Hazard Class:	-			
UN NA Number:	-			
Packing Group:	-			
RQ:	-			
Other - Tech Name:	-			
Other - Marine Pollutant:	-			

#### Notes:

- (1) When "Not regulated," enter the proper freight classification, "MSDS Number," and "Product Name" on the shipping paperwork.

Canadian TDG Hazard Class & PIN: Not regulated

### \*\*\* Section 15 - Regulatory Information \*\*\*

#### US Federal Regulations

##### A: General Product Information

All electrical equipment must be suitable for use in hazardous atmospheres involving aluminum powder in accordance with 29 CFR 1910.307. The National Electrical Code, NFPA 70, contains guidelines for determining the type and design of equipment and installation that will meet this requirement.

In reference to Title VI of the Clean Air Act of 1990, this material does not contain nor was it manufactured using ozone-depleting chemicals.

##### B: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

##### Aluminum (7429-90-5)

SARA 313: 1.0 % de minimis concentration (dust or fume only)

##### Manganese (7439-96-5)

SARA 313: 1.0 % de minimis concentration

# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

## Zinc (7440-66-6)

SARA 313: 1.0 % de minimis concentration (dust or fume only)

CERCLA: 1000 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is equal to or exceeds 0.004 inches); 454 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the solid metal released is equal to or exceeds 0.004 inches)

## Chromium (7440-47-3)

CERCLA: 5000 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is equal to or exceeds 0.004 inches); 2270 kg final RQ (no reporting of releases of this hazardous material is required if the diameter of the pieces of the solid metal released is equal to or exceeds 0.004 inches)

## Nickel (7440-02-0)

CERCLA: 100 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is equal to or exceeds 0.004 inches); 45.4 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is equal to or exceeds 0.004 inches)

### SARA 311/312 Physical and Health Hazard Categories:

**Immediate (acute) Health Hazard:** Yes, if particulates/fumes generated during processing.

**Delayed (chronic) Health Hazard:** Yes, if particulates/fumes generated during processing.

**Fire Hazard:** No

**Sudden Release of Pressure:** No

**Reactive:** Yes, if molten

### State Regulations

#### A: General Product Information

PENNSYLVANIA "Special Hazardous Substance": Chromium, Chromium compounds, hexavalent; Mineral oils; Nickel.

Chemical(s) known to the State of California to cause cancer: Chromium (hexavalent compounds), Nickel (metallic) and nickel compounds.

#### B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS #	CA	FL	MA	MN	NJ	PA
Aluminum	7429-90-5	Yes	No	Yes	Yes	Yes	Yes
Magnesium	7439-95-4	Yes	No	Yes	No	Yes	Yes
Manganese	7439-96-5	Yes	No	Yes	Yes	Yes	Yes
Silicon	7440-21-3	No	No	Yes	Yes	Yes	Yes
Zinc	7440-66-6	Yes	No	Yes	No	Yes	Yes
Chromium	7440-47-3	Yes	No	Yes	Yes	Yes	Yes
Nickel	7440-02-0	Yes	No	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer.

### Other Regulations

**A: General Product Information:** Material meets the criteria for inclusion in WHMIS D2A

#### B: Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Aluminum	7429-90-5	1 %
Manganese	7439-96-5	1 %
Chromium	7440-47-3	0.1 %

# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

## C: Component Analysis - Inventory

Component	CAS #	TSCA	DSL	EINECS	AUST.	MITI
Aluminum	7429-90-5	Yes	Yes	Yes	Yes	No
Magnesium	7439-95-4	Yes	Yes	Yes	Yes	No
Manganese	7439-96-5	Yes	Yes	Yes	Yes	No
Silicon	7440-21-3	Yes	Yes	Yes	Yes	No
Zinc	7440-66-6	Yes	Yes	Yes	Yes	No
Chromium	7440-47-3	Yes	Yes	Yes	Yes	No
Nickel	7440-02-0	Yes	Yes	Yes	Yes	No

## Inventory information

**MITI Inventory:** Pure metals are not specifically listed by CAS or MITI number on the MITI Inventory. However, the class of compounds for each of these metals is listed.

## \*\*\* Section 16 - Other Information \*\*\*

## MSDS History

Original: March 16, 1990  
Supersedes: August 20, 2003  
Revised: September 29, 2006

## MSDS Status

09/28/2006: Reviewed on a periodic basis in accordance with Alcoa policy. Changes in Sections 1, 2, 3, 4, 5, 7, 8, 9, 10, 11, 12 & 15.  
08/14/2003: Reviewed on a periodic basis in accordance with Alcoa policy. Changes in Sections 1, 2, 3, 8 and 15.

## Prepared By

Hazardous Materials Control Committee  
Preparer: Jon N. Peace, 412-553-2293/Stephanie Williams, 412-553-1479

## MSDS System Number

115951

## Other Information

- \* Aluminum Association's Bulletin F-1, "Guidelines for Handling Aluminum Fines Generated During Various Aluminum Fabricating Operations." The Aluminum Association, 900 19th Street, N.W., Washington, DC 20006.
- \* Aluminum Association, "Guidelines for Handling Molten Aluminum, The Aluminum Association, 900 19th Street, N.W., Washington, DC 20006.
- \* NFPA 65, Standard for Processing and Finishing of Aluminum (NFPA phone: 800-344-3555)
- \* NFPA 651, Standard for Manufacture of Aluminum and Magnesium Powder
- \* NFPA 70, Standard for National Electrical Code (Electrical Equipment, Grounding and Bonding)
- \* NFPA 77, Standard for Static Electricity
- \* Guide to Occupational Exposure Values-2006, Compiled by the American Conference of Governmental Industrial Hygienists (ACGIH).
- \* Documentation of the Threshold Limit Values and Biological Exposure Indices, Sixth Edition, 1991, Compiled by the American Conference of Governmental Industrial Hygienists, Inc. (ACGIH).
- \* NIOSH Pocket Guide to Chemical Hazards, U.S. Department of Health and Human Services, February 2004.
- \* Patty's Industrial Hygiene and Toxicology: Volume II: Toxicology, 4th ed., 1994, Patty, F. A.; edited by Clayton, G. D. and Clayton, F. E.: New York: John Wiley & Sons, Inc.
- \* expub, www.expub.com, Expert Publishing, LLC.

# Material Safety Data Sheet

Product Name: WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS

ID: 665

## Key-Legend:

ACGIH	American Conference of Governmental Industrial Hygienists
AICS	Australian Inventory of Chemical Substances
CAS	Chemical Abstract Service
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
CFR	Code of Federal Regulations
CPR	Cardio-pulmonary Resuscitation
DOT	Department of Transportation
DSL	Domestic Substances List (Canada)
ECOIN	European Core Inventory
EPA	Environmental Protection Act
IARC	International Agency for Research on Cancer
LC <sub>50</sub>	Lethal concentration (50 percent kill)
LC <sub>L0</sub>	Lowest published lethal concentration
LD <sub>50</sub>	Lethal dose (50 percent kill)
LD <sub>L0</sub>	Lowest published lethal dose
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
PIN	Product Identification Number
RCRA	Resource Conservation and Recovery Act
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit
TCLP	Toxic Chemicals Leachate Program
TDG	Transportation of Dangerous Goods
TLV	Threshold Limit Value
TSCA	Toxic Substance Control Act
TWA	Time Weighted Average
atm	atmosphere
cm	centimeter
g, gm	gram
in	inch
kg	kilogram
lb	pound
m	meter
mg	milligram
ml, ML	milliliter
mm	millimeter
n.o.s.	not otherwise specified
ppb	parts per billion
ppm	parts per million
psia	pounds per square inch absolute
u	micron
ug	microgram

INFORMATION HEREIN IS GIVEN IN GOOD FAITH AS AUTHORITATIVE AND VALID; HOWEVER, NO WARRANTY, EXPRESS OR IMPLIED, CAN BE MADE.

This is the end of MSDS # 665

# WROUGHT ALUMINUM PRODUCTS

## 3xxx SERIES ALLOYS

# CAUTION

**Physical Hazards:** Non-combustible as supplied. Small chips, fine turnings and dust from processing may be readily ignitable. Explosion potential may be present when: (1) dusts or fines are dispersed in the air, (2) fines, dust or molten aluminum are in contact with certain metal oxides (e.g. rust) or (3) chips, fines, dust or molten aluminum are in contact with water or moisture.

If coated with oil, may cause skin irritation/dermatitis by contact. Avoid skin contact.

**Health Hazards:** EYES: Dust or fume from processing: Can cause irritation. SKIN: Contact with residual oil/oil coating: Can cause irritation. Prolonged or repeated contact with the skin can cause dermatitis. Dust or fume from processing: Can cause sensitization and allergic contact dermatitis. INHALATION: Health effects from mechanical processing (e.g., cutting, grinding): Can cause irritation of respiratory tract. Additional health effects from elevated temperature processing (e.g., welding, melting): **Acute overexposures:** Can cause nausea, fever, chills, shortness of breath and malaise (metal fume fever).

**WARNING:** Chromium (hexavalent compounds), Nickel (metallic) and nickel compounds are chemicals known to the State of California to cause cancer.

**Precautions:** Avoid generating dust. Use with adequate ventilation. Keep material dry. Use appropriate personal protective equipment (safety glasses/gloves) to avoid injury. Use appropriate NIOSH approved respiratory protection (P95) if concentrations exceed the permissible limits.

**Fire Fighting:** Use Class D extinguishing agents on dusts, fines or molten metal. Use coarse water spray on chips and turnings.

**DO NOT USE:** Halogenated agents on small chips, dusts or fines, water around molten metal. These agents will react with the burning material.

**First Aid (dust or fume from processing):** EYES: Flush eyes with plenty of water or saline for at least 15 minutes. Consult a physician. SKIN: Wash skin with soap and water for at least 15 minutes. Consult a physician if irritation persists. INHALATION: Remove to fresh air. If unconscious or severely injured, check for clear airway, breathing and presence of pulse. Perform CPR if there is no pulse or respiration. Consult a physician.

Read Alcoa Material Safety Data Sheet No. 665 for more information about use and disposal.

Emergency Phone: (412) 553-4001.

INGREDIENTS:	CAS NUMBERS:	INGREDIENTS:	CAS NUMBERS:
Aluminum	(7429-90-5)	Zinc	(7440-66-6)
Magnesium	(7439-95-4)	Chromium	(7440-47-3)
Manganese	(7439-96-5)	Nickel	(7440-02-0)
Silicon	(7440-21-3)		

### Alcoa Inc.

201 Isabella Street, Pittsburgh, PA 15212-5858 USA



9/06 665