

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 1 of 24

SECTION 1. IDENTIFICATION

Product name : **LA LMM-6000**
GSLA_LMM-6000 Black Paste 250g

Product code : **1411218**

Manufacturer or supplier's details

Company name of supplier : Vibrantz Corporation

Address : 6060 Parkland Blvd. Suite 250
Mayfield Heights OH 44124-4185

Telephone : (216) 875-5600

E-mail address of person responsible for the SDS : PS.Request.americas@vibrantz.com

Emergency telephone number

In-Country Number : (800)424-9300

CHEMTREC Global Number : +(1)-703-527-3887(Call Collect)

Recommended use of the chemical and restrictions on use

Recommended use : Industrial use

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Acute toxicity (Oral) : Category 4

Flammable liquids : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Specific target organ toxicity : Category 1
- single exposure

Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure

Other hazards

None known.

GHS label elements

Hazard pictograms



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 2 of 24

H351 Suspected of causing cancer.
H370 Causes damage to organs.

Precautionary statements

:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 3 of 24

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Paint related material

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
ethanol	64-17-5*	>= 30 - <= 60	-
Trade Secret Molybdenum Compound		>= 15 - <= 40	TSI
Trade Secret Silicated compound		>= 5 - <= 10	TSI
ethyl acetate	141-78-6*	>= 3 - <= 7	-
Trade Secret Vanadium Compound		>= 1 - <= 5	TSI
2-butoxyethanol	111-76-2*	>= 1 - <= 5	-
methanol	67-56-1*	>= 1 - <= 5	-
propane-1,2-diol	57-55-6*	>= 0.5 - <= 1.5	-
(2-methoxymethylethoxy)propanol	34590-94-8*	>= 0.5 - <= 1.5	-
n-butyl acetate	123-86-4*	>= 0.1 - <= 1	-
4-methylpentan-2-one	108-10-1*	>= 0.1 - <= 1	-
quartz	14808-60-7*	>= 0.1 - <= 1	-
polyaminoamide	162627-17-0*	>= 0.1 - <= 1	-
1-methoxy-2-propanol	107-98-2*	>= 0.1 - <= 1	-
solvent naphtha (petroleum), light, aromatic	64742-95-6*	>= 0.1 - <= 1	-

* Indicates that the identifier is a CAS No.

TSI- the chemical identity is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Do not leave the victim unattended.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

If inhaled : Remove to fresh air.
If unconscious, place in recovery position and seek medical advice.
Never give anything by mouth to an unconscious person.

In case of skin contact : Wash off immediately with soap and plenty of water.
If a person feels unwell or symptoms of skin irritation appear, consult a physician.

In case of eye contact : Rinse immediately with plenty of water and seek medical ad-

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 4 of 24

If swallowed	:	vice. Do NOT induce vomiting. Rinse immediately with plenty of water and seek medical advice.
Most important symptoms and effects, both acute and delayed	:	May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Suspected of causing cancer. Causes damage to organs.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire-fighting	:	Do not allow run-off from fire fighting to enter drains or water courses. Do not use a solid water stream as it may scatter and spread fire.
Hazardous combustion products	:	No hazardous combustion products are known
Further information	:	Use a water spray to cool fully closed containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Ensure adequate ventilation. Follow safe handling advice and personal protective equipment recommendations.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. Prevent product from entering drains.
Methods and materials for containment and cleaning up	:	Sweep up and shovel into suitable containers for disposal. Clean contaminated floors and objects thoroughly while observing environmental regulations.

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 5 of 24

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.
Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Do not get in eyes or mouth or on skin.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Do not use in areas without adequate ventilation.
Keep away from heat and sources of ignition.

Conditions for safe storage : Keep in a dry, cool and well-ventilated place.
Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanol	64-17-5	STEL	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
Trade Secret Molybdenum Compound	Not Assigned	TWA	5 mg/m3 (Molybdenum)	OSHA Z-1
		TWA (Respirable particulate matter)	0.5 mg/m3 (Molybdenum)	ACGIH
		TWA	5 mg/m3 (Molybdenum)	OSHA P0
		TWA (total dust)	15 mg/m3 (Molybdenum)	OSHA Z-1
		TWA (Inhalable particulate matter)	10 mg/m3 (Molybdenum)	ACGIH
		TWA (Respirable particulate matter)	3 mg/m3 (Molybdenum)	ACGIH
		TWA (Total dust)	10 mg/m3 (Molybdenum)	OSHA P0
Trade Secret Silicated compound	Not Assigned	TWA (Respirable particulate matter)	0.1 mg/m3	ACGIH

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g		
Product specification	RS_FP_603463	Revision Date	07/22/2026	
Version	4.6	Print Date	07/22/2026	
Material number	1411218	Page	Page 6 of 24	

		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	3 mg/m3	NIOSH REL
		TWA (respirable dust fraction)	3 mg/m3	OSHA P0
ethyl acetate	141-78-6	TWA	400 ppm	ACGIH
		TWA	400 ppm 1,400 mg/m3	NIOSH REL
		TWA	400 ppm 1,400 mg/m3	OSHA Z-1
		TWA	400 ppm 1,400 mg/m3	OSHA P0
Trade Secret Vanadium Compound	Not Assigned	C (Dust)	0.05 mg/m3 (Vanadium)	NIOSH REL
		C (Fumes)	0.05 mg/m3 (Vanadium)	NIOSH REL
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		TWA	200 ppm 260 mg/m3	OSHA P0
		STEL	250 ppm 325 mg/m3	OSHA P0
propane-1,2-diol	57-55-6	TWA	10 mg/m3	US WEEL
(2-methoxymethylethoxy)propanol	34590-94-8	TWA	100 ppm 600 mg/m3	NIOSH REL
		ST	150 ppm 900 mg/m3	NIOSH REL
		TWA	100 ppm 600 mg/m3	OSHA Z-1
		TWA	100 ppm 600 mg/m3	OSHA P0
		STEL	150 ppm 900 mg/m3	OSHA P0
		TWA	50 ppm	ACGIH
n-butyl acetate	123-86-4	TWA	150 ppm	NIOSH REL

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 7 of 24

			710 mg/m3	
		ST	200 ppm 950 mg/m3	NIOSH REL
		TWA	150 ppm 710 mg/m3	OSHA Z-1
		STEL	200 ppm 950 mg/m3	OSHA P0
		TWA	150 ppm 710 mg/m3	OSHA P0
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
4-methylpentan-2-one	108-10-1	TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
		TWA	50 ppm 205 mg/m3	NIOSH REL
		ST	75 ppm 300 mg/m3	NIOSH REL
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	50 ppm 205 mg/m3	OSHA P0
		STEL	75 ppm 300 mg/m3	OSHA P0
quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
1-methoxy-2-propanol	107-98-2	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		ST	150 ppm 540 mg/m3	NIOSH REL
		TWA	100 ppm 360 mg/m3	NIOSH REL
		TWA	100 ppm 360 mg/m3	OSHA P0
		STEL	150 ppm 540 mg/m3	OSHA P0
		TWA	2 ppm	US WEEL

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 8 of 24

		STEL	5 ppm	US WEEL
solvent naphtha (petroleum), light, aromatic	64742-95-6	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI
4-methylpentan-2-one	108-10-1	methyl iso-butyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI
2-butoxyethanol	111-76-2	Butoxyace-tic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g creatinine	ACGIH BEI

Engineering measures : Apply technical measures to comply with the occupational exposure limits.
Provide adequate ventilation.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection
Material : Protective gloves

Eye protection : Safety glasses with side-shields
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Impervious clothing
Protective measures : Wear suitable protective equipment.
Hygiene measures : Remove contaminated clothing and protective equipment before entering eating areas.
Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 9 of 24

Appearance	:	paste
Colour	:	yellow
Odour	:	characteristic
Odour Threshold	:	No data available
pH	:	No data available
Melting point/ range	:	No data available
Flash point	:	57 °F / 14 °C
Evaporation rate	:	No data available
Burning rate	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	23 %(V)
Lower explosion limit / Lower flammability limit	:	1.1 %(V)
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	No data available
Bulk density	:	No data available
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 10 of 24

Auto-ignition temperature	: not determined
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Explosive properties	: No data available
Oxidizing properties	: Not applicable
Refractive index	: No data available
Volatile organic compounds (VOC) content	: 50 %

This product contains components that are reportable under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489).

This product does not contain any VOC exemptions listed under the U.S. Clean Air Act Section 450.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Incompatible materials Heat, flames and sparks.
Incompatible materials	: Incompatible with oxidizing agents. Incompatible with strong acids and bases. Not applicable
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

inhalation (dust/mist/fume)

inhalation (vapour)

Skin

Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	: Acute toxicity estimate: 2,620 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate: 58.96 mg/l Exposure time: 4 h

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 11 of 24

Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

ethanol:

Acute oral toxicity : LD50 Oral (Rat, male and female): 10,470 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 51 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

Trade Secret Molybdenum Compound:

Acute oral toxicity : LD50 (Rat, male and female): 4,461 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat, male and female): > 5,840 mg/m3
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Target Organs: Mucous membranes
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No adverse effect has been observed in acute toxicity tests.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 6,100 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 22.5 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 18,000 mg/kg

Trade Secret Vanadium Compound:

Acute oral toxicity : LD50 (Rat, male and female): 275.87 mg/kg
Method: OECD Test Guideline 401

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 12 of 24

GLP: yes

2-butoxyethanol:

Acute oral toxicity : LD50 Oral (Rat, male and female): 1,200 mg/kg
Method: OECD Test Guideline 401
GLP: no

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

methanol:

Acute oral toxicity : LD50 Oral (Rat): 6,200 mg/kg

propane-1,2-diol:

Acute oral toxicity : LD50 Oral (Rat): 20 g/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 20,800 mg/kg

(2-methoxymethylethoxy)propanol:

Acute oral toxicity : LD50 (Rat, male and female): 5,400 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit, male): 9,510 mg/kg
Method: OECD Test Guideline 402

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 10,768 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 17,600 mg/kg

4-methylpentan-2-one:

Acute oral toxicity : LD50 Oral (Rat): 2,080 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3,000 mg/kg

quartz:

Acute oral toxicity : LD50 Oral (Rat): 500 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral (Rat, male and female): 5,612 - 6,348 mg/kg
Method: OECD Test Guideline 401
GLP: no
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50: 56.6 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 13 of 24

Acute dermal toxicity : LD50 Dermal (Rabbit): 15,800 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

solvent naphtha (petroleum), light, aromatic:

Acute oral toxicity : LD50 Oral (Rat, male and female): 8,400 mg/kg

Acute inhalation toxicity : LC50 (Rat): 8,000 - 10,000 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: yes

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): $\geq$ 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation

Not classified based on available information.

Components:

ethanol:

Species : Rabbit
Exposure time : 24 h
Method : OECD Test Guideline 404
Result : No skin irritation

Trade Secret Molybdenum Compound:

Species : Rabbit
Exposure time : 4 h
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

2-butoxyethanol:

Species : Rabbit
Exposure time : 72 h
Method : OECD Test Guideline 404
Result : Irritating to skin.
GLP : yes

(2-methoxymethylethoxy)propanol:

Species : Rabbit
Result : No skin irritation

1-methoxy-2-propanol:

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.4.
Result : No skin irritation

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 14 of 24

GLP : yes

solvent naphtha (petroleum), light, aromatic:

Species : Rabbit
Result : Mild skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

ethanol:

Species : Rabbit
Result : Eye irritation
Method : OECD Test Guideline 405

Trade Secret Molybdenum Compound:

Species : Rabbit
Result : Irritating to eyes.
Assessment : Irritating to eyes.

ethyl acetate:

Species : Rabbit
Result : No eye irritation

Trade Secret Vanadium Compound:

Species : Rabbit
Result : Irritating to eyes.
Exposure time : 1 h
Method : OECD Test Guideline 405
GLP : yes

2-butoxyethanol:

Result : Eye irritation

(2-methoxymethylethoxy)propanol:

Species : Rabbit
Result : Irritation to eyes, reversing within 7 days
Exposure time : 24 h

1-methoxy-2-propanol:

Species : Rabbit
Result : No eye irritation
Method : Directive 67/548/EEC, Annex V, B.5.
GLP : yes

solvent naphtha (petroleum), light, aromatic:

Species : Rabbit

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 15 of 24

Result : Mild eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

1-methoxy-2-propanol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : Directive 67/548/EEC, Annex V, B.6.
Result : Does not cause skin sensitisation.
GLP : yes

Germ cell mutagenicity

Not classified based on available information.

Components:

solvent naphtha (petroleum), light, aromatic:

Germ cell mutagenicity - : Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.
Assessment

Carcinogenicity

Suspected of causing cancer.

IARC	Group 2B: Possibly carcinogenic to humans	
	4-methylpentan-2-one	108-10-1
	Trade Secret Molybdenum Compound	Not Assigned
OSHA	OSHA specifically regulated carcinogen	
	quartz (crystalline silica)	14808-60-7
NTP	Known to be human carcinogen	
	quartz (Silica, Crystalline (Respirable Size))	14808-60-7

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.
Causes damage to organs.

Components:

Trade Secret Molybdenum Compound:

Assessment : May cause respiratory irritation.

Trade Secret Vanadium Compound:

Assessment : May cause respiratory irritation.

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 16 of 24

1-methoxy-2-propanol:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

solvent naphtha (petroleum), light, aromatic:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

solvent naphtha (petroleum), light, aromatic:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

ethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 12,340 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l
End point: Growth rate
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

EC10 (Chlorella vulgaris (Fresh water algae)): 11.5 mg/l
Exposure time: 72 h
Test Type: static test

Trade Secret Molybdenum Compound:

Toxicity to fish : (Oncorhynchus mykiss (rainbow trout)): 100 mg/l
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

(Pimephales promelas (fathead minnow)): 370 mg/l
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other : (Daphnia magna (Water flea)): 100 mg/l

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 17 of 24

aquatic invertebrates

Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility

(Daphnia magna (Water flea)): 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility

ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 220 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 560 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): 3,300 mg/l
Exposure time: 48 h

Trade Secret Vanadium Compound:

Toxicity to fish : LC50 (Marine species): 27.8 mg/l
Exposure time: 96 h
Test Type: flow-through test

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

2-butoxyethanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,490 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,800 mg/l
Exposure time: 48 h

methanol:

Toxicity to fish : LC50 (Fish): 28,200 mg/l
Exposure time: 96 h

propane-1,2-diol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 51,400 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): > 10,000 mg/l
Exposure time: 96 h

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 18 of 24

Toxicity to algae/aquatic plants : EC50 (algae): 19,000 mg/l
Exposure time: 96 h

(2-methoxymethylethoxy)propanol:

Toxicity to fish : LC50 (Fish): 10,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): 1,919 mg/l
Exposure time: 48 h

n-butyl acetate:

Toxicity to fish : LC50 (Fish): 17 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 72.8 mg/l
Exposure time: 24 h

Toxicity to algae/aquatic plants : EC50 (algae): 674.7 mg/l
Exposure time: 72 h

4-methylpentan-2-one:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 496 - 514 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 170 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 400 mg/l
Exposure time: 96 h

1-methoxy-2-propanol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 4,600 - 10,000 mg/l
Exposure time: 96 h
Test Type: static test
Method: DIN 38412
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 23,300 mg/l
Exposure time: 48 h
Test Type: static test
Method: ISO TC147/SC5/WG2
GLP: yes

Ecotoxicology Assessment

Acute aquatic toxicity : No toxicity at the limit of solubility

Chronic aquatic toxicity : No toxicity at the limit of solubility

solvent naphtha (petroleum), light, aromatic:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l
Exposure time: 96 h

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 19 of 24

Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 12 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (algae)): 1.1 mg/l
Exposure time: 72 h
Test Type: static test

Persistence and degradability

Components:

ethanol:

Biodegradability : aerobic
Result: Readily biodegradable.
Biodegradation: 97 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

1-methoxy-2-propanol:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301
GLP: yes

Bioaccumulative potential

Components:

ethanol:

Bioaccumulation : Bioconcentration factor (BCF): 0.66
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: -0.35 (75 °F / 24 °C)
pH: 7.4
Method: OECD Test Guideline 107

ethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 0.73 (68 °F / 20 °C)

2-butoxyethanol:

Partition coefficient: n-octanol/water : log Pow: 0.77 (68 °F / 20 °C)
pH: 7

methanol:

Partition coefficient: n-octanol/water : log Pow: -0.77

(2-methoxymethylethoxy)propanol:

Partition coefficient: n-octanol/water : log Pow: -0.064 (68 °F / 20 °C)

n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3 (77 °F / 25 °C)
Method: OECD Test Guideline 117

4-methylpentan-2-one:

Partition coefficient: n- : Pow: 1.19

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 20 of 24

octanol/water

1-methoxy-2-propanol:

Partition coefficient: n-octanol/water : log Pow: 0.37 (68 °F / 20 °C)
pH: 6.8
Method: OECD Test Guideline 117

solvent naphtha (petroleum), light, aromatic:

Partition coefficient: n-octanol/water : log Pow: 3.42 - 3.9

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.
Dispose of wastes in an approved waste disposal facility.
Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1263
Proper shipping name : PAINT RELATED MATERIAL
Class : 3
Packing group : II
Labels : 3
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : Paint related material
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 21 of 24

Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT RELATED MATERIAL
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1263
Proper shipping name : Paint related material
Class : 3
Packing group : II
Labels : FLAMMABLE LIQUID
ERG Code : 128
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethyl acetate	141-78-6	100	100 (F003)
methanol	67-56-1	100	100 (F003)
4-methylpentan-2-one	108-10-1	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Respiratory or skin sensitisation
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Serious eye damage or eye irritation

SARA 313 : This product contains components that are reportable under the regulation.

Molybdenum trioxide
Vanadium compounds
Certain Glycol Ethers
Methanol

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 22 of 24

Methyl isobutyl ketone

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product contains components that are reportable under the hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product contains components that are reportable under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product contains components that are reportable under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product contains components that are reportable under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

This product contains components that are reportable under the regulation.

Pennsylvania Right To Know

This product contains components that are reportable under the regulation.

Maine Chemicals of High Concern

This product contains components that are reportable under the regulation.

Vermont Chemicals of High Concern

This product contains components that are reportable under the regulation.

Washington Chemicals of High Concern

Product does not contain any listed chemicals

New Jersey Right To Know

This product contains components that are reportable under the regulation.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

California List of Hazardous Substances

This product contains components that are reportable under the regulation.

California Permissible Exposure Limits for Chemical Contaminants

This product contains components that are reportable under the regulation.

California Regulated Carcinogens

This product contains components that are reportable under the regulation.

The components of this product are reported in the following inventories:

TCSI (Taiwan) : On the inventory, or in compliance with the inventory

EINECS (European Union) : On the inventory, or in compliance with the inventory

TSCA (United States) : All substances listed as active on the TSCA inventory

AIRC (Australia) : All components are listed on the inventory, regulatory obliga-

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 23 of 24

DSL/NDL (Canada)	: tions/restrictions apply This product contains the following components listed on the Canadian NDSL. All other components are on the Canadian DSL. polyaminoamide
ENCS (Japan)	: On the inventory, or in compliance with the inventory
ISHL (Japan)	: Not in compliance with the inventory
KECI (Korea)	: On the inventory, or in compliance with the inventory
NZioC (New Zealand)	: On the inventory, or in compliance with the inventory
PICCS (Philippines)	: Not in compliance with the inventory
IECSC (China)	: On the inventory, or in compliance with the inventory
SWISS (Switzerland)	: On the inventory, or in compliance with the inventory
TECI (Thailand)	: Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
US WEEL	: USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA CARC / PEL	: Permissible exposure limit (PEL)
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average
US WEEL / TWA	: 8-hr TWA
US WEEL / STEL	: Short-Term TWA

SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2024)

LA LMM-6000		GSLA_LMM-6000 Black Paste 250g	
Product specification	RS_FP_603463	Revision Date	07/22/2026
Version	4.6	Print Date	07/22/2026
Material number	1411218	Page	Page 24 of 24

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/22/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN