

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 1 of 22

SECTION 1. IDENTIFICATION

Product name : **ULTRA Black Spray**
CerMark ULTRA 2oz. Aerosol
Product code : **1436338**

Manufacturer or supplier's details

Company name of supplier : Vibrantz Corporation
Address : 6060 Parkland Blvd. Suite 250
Mayfield Heights OH 44124-4185
Telephone : (216) 875-5600
E-mail address of person responsible for the SDS : PS.Request.americas@vibrantz.com

Emergency telephone number

In-Country Number : (800)424-9300
CHEMTREC Global Number : +(1)-703-527-3887 (Call Collect)

Recommended use of the chemical and restrictions on use

Recommended use : Industrial use

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols : Category 1
Eye irritation : Category 2A
Skin sensitisation : Category 1
Carcinogenicity : Category 2

GHS label elements

Hazard pictograms :   
Signal word : Danger
Hazard statements : H222 Extremely flammable aerosol.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 2 of 22

Precautionary statements	:	Prevention: P201 P202 P210 P211 P251 P261 P264 P272 P280	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist. Wash skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response: P302 + P352 P305 + P351 + P338 P308 + P313 P333 + P313 P337 + P313 P363	IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse.
		Storage: P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
		Disposal: P501	Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	organic solvent inorganic pigment inorganic metal-nonmetal compound

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 3 of 22

silicon/siloxane
silicatic material
metal/metal compound
extremely flammable liquefied gas
hydrocarbon, aliphatic

Components

Chemical name	CAS-No.	Concentration (% w/w)
ethanol	64-17-5	>= 30 - < 50
butane	106-97-8	>= 10 - < 20
isobutane	75-28-5	>= 5 - < 10
Molybdenum(VI) oxide	1313-27-5	>= 5 - < 10
propane	74-98-6	>= 5 - < 10
mica	12001-26-2	>= 5 - < 10
silicon	7440-21-3	>= 1 - < 5
manganese	7439-96-5	>= 1 - < 5
2-butoxyethanol	111-76-2	>= 1 - < 5
ethyl acetate	141-78-6	>= 1 - < 5
Silica, amorphous	112945-52-5	>= 0.1 - < 1
polyaminoamide	162627-17-0	>= 0.1 - < 1
4-methylpentan-2-one	108-10-1	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Do not leave the victim unattended.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical advice.

In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
If skin irritation persists, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Rinse mouth immediately with plenty of water and seek medical advice.
Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

Most important symptoms : May cause an allergic skin reaction.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 4 of 22

and effects, both acute and delayed Causes serious eye irritation.
Suspected of causing cancer.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

Further information : Use a water spray to cool fully closed containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.
Clean contaminated floors and objects thoroughly while ob-

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 5 of 22

serving environmental regulations.

Clean contaminated floors and objects thoroughly while observing environmental regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Avoid release to the environment. Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanol	64-17-5	STEL	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m ³	NIOSH REL
		TWA	1,000 ppm	OSHA Z-1

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray

Product specification **RS_FP_606724**
Version **2.1**
Material number **1436338**

CerMark ULTRA 2oz. Aerosol

Revision Date **11/20/2024**
Print Date **11/26/2024**
Page **Page 6 of 22**

			1,900 mg/m3	
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		STEL	1,000 ppm	ACGIH
isobutane	75-28-5	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		STEL	1,000 ppm	ACGIH
Molybdenum(VI) oxide	1313-27-5	TWA	5 mg/m3 (Molybdenum)	OSHA Z-1
		TWA (Respirable particulate matter)	0.5 mg/m3 (Molybdenum)	ACGIH
		TWA	5 mg/m3 (Molybdenum)	OSHA P0
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
mica	12001-26-2	TWA (Respirable particulate matter)	0.1 mg/m3	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	3 mg/m3	NIOSH REL
		TWA (respirable dust fraction)	3 mg/m3	OSHA P0
silicon	7440-21-3	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
manganese	7439-96-5	TWA (Fumes)	1 mg/m3 (Manganese)	NIOSH REL
		ST (Fumes)	3 mg/m3 (Manganese)	NIOSH REL

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray

Product specification **RS_FP_606724**
Version **2.1**
Material number **1436338**

CerMark ULTRA 2oz. Aerosol

Revision Date **11/20/2024**
Print Date **11/26/2024**
Page **Page 7 of 22**

		C (Fumes)	5 mg/m3	OSHA Z-1
		TWA (Fumes)	1 mg/m3 (Manganese)	OSHA P0
		STEL (Fumes)	3 mg/m3 (Manganese)	OSHA P0
		TWA (Inhalable particulate matter)	0.1 mg/m3 (Manganese)	ACGIH
		TWA (Respirable particulate matter)	0.02 mg/m3 (Manganese)	ACGIH
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
ethyl acetate	141-78-6	TWA	400 ppm	ACGIH
		TWA	400 ppm 1,400 mg/m3	NIOSH REL
		TWA	400 ppm 1,400 mg/m3	OSHA Z-1
		TWA	400 ppm 1,400 mg/m3	OSHA P0
Silica, amorphous	112945-52-5	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m3 (Silica)	NIOSH REL
4-methylpentan-2-one	108-10-1	TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
		TWA	50 ppm 205 mg/m3	NIOSH REL
		ST	75 ppm 300 mg/m3	NIOSH REL
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	50 ppm 205 mg/m3	OSHA P0
		STEL	75 ppm 300 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-butoxyethanol	111-76-2	Butoxyacet-	Urine	End of	200 mg/g	ACGIH

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol				
Product specification	RS_FP_606724	Revision Date	11/20/2024			
Version	2.1	Print Date	11/26/2024			
Material number	1436338	Page	Page 8 of 22			

		tic acid (BAA)		shift (As soon as possible after exposure ceases)	Creatinine	BEI
4-methylpentan-2-one	108-10-1	methyl iso-butyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI

Engineering measures : Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

In the case of vapour formation use a respirator with an approved filter.

In the case of dust or aerosol formation use respirator with an approved filter.

Hand protection : Wear protective gloves, for example: polyvinyl alcohol or nitrile-butyl-rubber gloves, or similar; Glove thickness: > 0.4 mm and Break Through time: > 480 minutes. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Before removing gloves clean them with soap and water.

Eye protection : Ensure that eyewash stations and safety showers are close to the workstation location.
Tightly fitting safety goggles.

Skin and body protection : Impervious clothing

Protective measures : Wear suitable protective equipment.

Hygiene measures : Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 9 of 22

Remove contaminated clothing and protective equipment before entering eating areas.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	aerosol
Odour	:	characteristic
Odour Threshold	:	No data available
pH	:	No data available
Melting point/range	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	-155 °F / -104 °C Method: calculated
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Burning rate	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	19 %(V)
Lower explosion limit / Lower flammability limit	:	1.1 %(V)
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Bulk density	:	No data available

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 10 of 22

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Explosive properties : No data available

Oxidizing properties : Not applicable

Volatile organic compounds (VOC) content : This product contains components that are reportable under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

This product does not contain any VOC exemptions listed under the U.S. Clean Air Act Section 450.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available

Not applicable

Hazardous decomposition products : No data available

Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray	CerMark ULTRA 2oz. Aerosol
Product specification	RS_FP_606724
Version	2.1
Material number	1436338
	Revision Date 11/20/2024
	Print Date 11/26/2024
	Page Page 11 of 22

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

ethanol:

Acute oral toxicity : LD50 Oral (Rat, male and female): 10,470 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 51 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

butane:

Acute inhalation toxicity : LC50 (Rat, male and female): 658 g/m3
Exposure time: 4 h
Test atmosphere: gas

Molybdenum(VI) oxide:

Acute oral toxicity : LD50 (Rat, male and female): 4,461 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat, male and female): > 5,840 mg/m3
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Target Organs: Mucous membranes
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No adverse effect has been observed in acute toxicity tests.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 12 of 22

toxicity

propane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

silicon:

Acute oral toxicity : LD50 Oral (Rat): 3,160 mg/kg

manganese:

Acute oral toxicity : LD50 Oral (Rat): 9 g/kg

2-butoxyethanol:

Acute oral toxicity : LD50 Oral (Rat, male and female): 1,200 mg/kg
Method: OECD Test Guideline 401
GLP: no

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 6,100 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 22.5 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 18,000 mg/kg

Silica, amorphous:

Acute oral toxicity : LD50 Oral (Rat): 3,160 mg/kg

4-methylpentan-2-one:

Acute oral toxicity : LD50 Oral (Rat): 2,080 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

ethanol:

Species : Rabbit
Exposure time : 24 h

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 13 of 22

Method : OECD Test Guideline 404
Result : No skin irritation

Molybdenum(VI) oxide:

Species : Rabbit
Exposure time : 4 h
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

2-butoxyethanol:

Species : Rabbit
Exposure time : 72 h
Method : OECD Test Guideline 404
Result : Irritating to skin.
GLP : yes

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

ethanol:

Species : Rabbit
Result : Eye irritation
Method : OECD Test Guideline 405

Molybdenum(VI) oxide:

Species : Rabbit
Result : Irritating to eyes.
Assessment : Irritating to eyes.

silicon:

Species : Rabbit
Result : Mild eye irritation
Method : Draize Test

2-butoxyethanol:

Result : Eye irritation

ethyl acetate:

Species : Rabbit
Result : No eye irritation

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray	CerMark ULTRA 2oz. Aerosol
Product specification	RS_FP_606724
Version	2.1
Material number	1436338
	Revision Date 11/20/2024
	Print Date 11/26/2024
	Page Page 14 of 22

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

IARC	Group 2B: Possibly carcinogenic to humans Molybdenum(VI) oxide	1313-27-5
	Group 2B: Possibly carcinogenic to humans 4-methylpentan-2-one	108-10-1

OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
------	--

NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
-----	---

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

Molybdenum(VI) oxide:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 15 of 22

Components:

ethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 12,340 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l
End point: Growth rate
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

EC10 (Chlorella vulgaris (Fresh water algae)): 11.5 mg/l
Exposure time: 72 h
Test Type: static test

Molybdenum(VI) oxide:

Toxicity to fish : (Oncorhynchus mykiss (rainbow trout)): 100 mg/l
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

(Pimephales promelas (fathead minnow)): 370 mg/l
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 100 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility

(Daphnia magna (Water flea)): 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility

2-butoxyethanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,490 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,800 mg/l
Exposure time: 48 h

ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 220 mg/l

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 16 of 22

Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 560 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): 3,300 mg/l
Exposure time: 48 h

4-methylpentan-2-one:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 496 - 514 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 170 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 400 mg/l
Exposure time: 96 h

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

ethanol:

Biodegradability : aerobic
Result: Readily biodegradable.
Biodegradation: 97 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

ethanol:

Bioaccumulation : Bioconcentration factor (BCF): 0.66
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: -0.35 (75 °F / 24 °C)
pH: 7.4
Method: OECD Test Guideline 107

butane:

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 17 of 22

Partition coefficient: n-octanol/water : log Pow: 2.745

2-butoxyethanol:

Partition coefficient: n-octanol/water : log Pow: 0.77 (68 °F / 20 °C)
pH: 7

ethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 0.73 (68 °F / 20 °C)

4-methylpentan-2-one:

Partition coefficient: n-octanol/water : Pow: 1.19

Mobility in soil

Product:

Distribution among environmental compartments : Remarks: No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.
Dispose of wastes in an approved waste disposal facility.
The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 18 of 22

Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No.	:	UN 1950
Proper shipping name	:	Aerosols, flammable
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	Flammable Gas
Packing instruction (cargo aircraft)	:	203
Packing instruction (passenger aircraft)	:	203

IMDG-Code

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number	:	UN 1950
Proper shipping name	:	Aerosols
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	FLAMMABLE GAS
ERG Code	:	126
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 19 of 22

		(lbs)	(lbs)
4-methylpentan-2-one	108-10-1	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Respiratory or skin sensitisation
Carcinogenicity
Serious eye damage or eye irritation

SARA 313 : This product contains components that are reportable under the regulation.

Chromium III CompoundsCobalt, inorganic compounds
Molybdenum trioxide
Manganese
Certain Glycol Ethers
Methyl isobutyl ketone

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product contains components that are reportable under the hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product contains components that are reportable under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product contains components that are reportable under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product contains components that are reportable under the U.S. Clean Water Act Section 307.

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

This product contains components that are reportable under the regulation.

Massachusetts Right To Know

This product contains components that are reportable under the regulation.

Pennsylvania Right To Know

This product contains components that are reportable under the regulation.

Pennsylvania Right To Know

This product contains components that are reportable under the regulation.

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray	CerMark ULTRA 2oz. Aerosol
Product specification	RS_FP_606724
Version	2.1
Material number	1436338
	Revision Date 11/20/2024
	Print Date 11/26/2024
	Page Page 20 of 22

Maine Chemicals of High Concern

This product contains components that are reportable under the regulation.

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

This product contains components that are reportable under the regulation.

Washington Chemicals of High Concern

This product contains components that are reportable under the regulation.

New Jersey Right To Know

This product contains components that are reportable under the regulation.

New Jersey Right To Know

This product contains components that are reportable under the regulation.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

California List of Hazardous Substances

This product contains components that are reportable under the regulation.

California Permissible Exposure Limits for Chemical Contaminants

This product contains components that are reportable under the regulation.

The components of this product are reported in the following inventories:

TCSI (Taiwan)	: On the inventory, or in compliance with the inventory
TSCA (United States)	: All substances listed as active on the TSCA inventory
AIIC (Australia)	: Not in compliance with the inventory
DSL/NDSL (Canada)	: This product contains the following components listed on the Canadian NDSL. All other components are on the Canadian DSL. boron orthophosphate fatty acids, C16-22, ammonium salts polyaminoamide
ENCS (Japan)	: On the inventory, or in compliance with the inventory
ISHL (Japan)	: Not in compliance with the inventory
KECI (Korea)	: On the inventory, or in compliance with the inventory
PICCS (Philippines)	: Not in compliance with the inventory
IECSC (China)	: On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray	CerMark ULTRA 2oz. Aerosol
Product specification	RS_FP_606724
Version	2.1
Material number	1436338
	Revision Date 11/20/2024
	Print Date 11/26/2024
	Page Page 21 of 22

NZiC (New Zealand)	: Not in compliance with the inventory
SWISS (Switzerland)	: On the inventory, or in compliance with the inventory
EINECS (European Union)	: On the inventory, or in compliance with the inventory
CICR (Turkey)	: Not in compliance with the inventory
TECI (Thailand)	: Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-1 / C	: Ceiling
OSHA Z-3 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - In-

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200
(HCS 2012)

ULTRA Black Spray		CerMark ULTRA 2oz. Aerosol	
Product specification	RS_FP_606724	Revision Date	11/20/2024
Version	2.1	Print Date	11/26/2024
Material number	1436338	Page	Page 22 of 22

ternational Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 11/20/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN