

Magic^{AP}FILMTM

ALL-PURPOSE UV DECAL TRANSFER FILM

INNOVATIVE PRODUCTS TO BRING
YOUR AWESOME DESIGN TO LIFE

Magic Film is an excellent alternative to stickers and cut vinyl products. Magic Film is extremely durable, offering scuff and scratch resistance with a tough protective finish.



Magic Film has an aggressive adhesive which provides superior adhesion to a wide variety of HARD surfaces. Magic Film is the answer for short run product customization, without large minimum order quantities.

MAGIC^{AP}FILMTM

ALL-PURPOSE UV DECAL TRANSFER FILM

INNOVATIVE PRODUCTS TO BRING YOUR AWESOME DESIGN TO LIFE

Magic Film decals are an excellent alternative to stickers and cut vinyl products.

Magic Film decals are extremely durable, offering scuff and scratch resistance with a tough protective finish. Magic Film decals are also capable of withstanding exposure to harsh chemicals and cleaning solutions. Magic Film decals have an aggressive adhesive which provides superior adhesion to a wide variety of surfaces. Magic Film decals are the answer for short run product customization, without large minimum order quantities (MOQ's). Ideal for decorating difficult surfaces that are not capable of being directly printed to.

Magic Film decals applications are limited only by your imagination!

PROCESSING INSTRUCTIONS FOR MAGIC FILM (AP) ALL PURPOSE

1 – With adhesive side of White Paper A-Film facing up (Clear Protective Film Up), secure to print bed using vacuum.

If your printer does not have vacuum, secure A-Film to metal plate or other rigid support material using tape around all 4 edges.

NOTE: With this method, you must first remove the protective clear film from the adhesive surface.

2 – If A-Film has been secured to metal plate or other rigid support material, place on print bed and proceed to step (3). If A-Film is secured to print bed by vacuum, proceed to next step (2a).

2a – Once A-Film is secured, remove the protective (clear) face liner from the White Adhesive Paper and proceed to next step.

3 – RIP image, Wx1, C, M, Y, K, Varnish (Clear) Top Coat and start printing. **IMPORTANT!** Quality and Durability of the transfer decal produced is determined by the following factors. First, the most important factor is the ink set that is installed in your printer. If the ink set installed is “too hard”, the decal may crack or fracture when being applied to surfaces with complex curvatures or sharp corners. Conversely, if the ink set installed is “too flexible/soft”, the decal will tend to bubble or have an orange peel effect. This phenomenon will happen during application, or after it has been applied. Refer to recommended printers, ink sets, and layering instructions. The second important factor is which layering structure option you choose. Refer to layering structure options, found in the printers, ink sets, and layering instructions.

4 - After artwork has finished printing, you are now ready to apply the B-Film (clear transfer film) to the printed surface of the A-Film. Using firm pressure only, COLD laminate B-Film and A-Film together. Cover the artwork on A-Film with B-Film **FACING DOWN**. It is recommended using a laminator for this process. If a laminator is not available, use a metal plate, squeegee, or other rigid support material when applying Transfer B-Film. It is important to eliminate bubbles, tunneling, and creases between images(s) on A-Film and Transfer B-Film. Bubbles and creases between the two films can lead to fine type and lettering not properly transferring onto intended surface.

5 - Cut out desired image(s) using scissors, razor blade or plotter cutter.

6 - Separating A and B Film for decal application.

NOTE: For best results, we recommend that you use the following procedure:

A. With decal cut out, the A-Film's white backing should be facing up, with artwork and laminated B-Film **FACING DOWN**.

B. Hold a common corner of the decal and begin separating the A and B Film with your fingertips. Then hold the exposed/separated corner of the B-Film with one set of fingertips, and with the other set start to **GENTLY** roll back the white backing from the B-Film. Continue rolling back the white backing, while at the same time slowly pulling away the B-Film. When doing this, continue checking to ensure that all artwork is properly releasing from the A-Film, and transferring onto the B-Film. If images/ink starts to "hang back", lay the A-Film back down and press on the B-Film to help recapture the held back images/ink. If necessary, repeat until all artwork is attached to B-Film and completely separated from the A-Film. Discard white paper backing, and you are ready to apply your Magic Film decal.

7 - Applying Decal. Care should be taken applying decal, to avoid trapping air bubbles between decal and target surface. Clean all surfaces with alcohol to help ensure proper adhesion. Place decal onto object to be decorated.

NOTE: Make sure that decal is properly placed in its intended location. Once decal comes in contact with surface, it **CANNOT** be repositioned. Rub/press firmly over entire image area of decal to ensure that it is completely adhered. Using slow to medium speed, peel the Transfer B-Film away. **NOTE:** For some applications, you may find it helpful to apply warm air to the surface of the decal for 5-10 seconds using a standard hair dryer, **PRIOR** to peeling the Transfer B-Film away. **DO NOT** use a heat gun, as it can potentially melt the decal. This procedure will help soften the adhesive outside of the image area, making it more easy to remove from the target surface.

MAGIC FILM STORAGE:

NOTE: When possible, keep Magic Film in its original packaging, stored flat in a cool dry place.

It is recommended to use finished Magic Film decals within 2-4 weeks after printing.